

## 三相 63A 自复式过欠压保护器

Three phase 63A self-reset over voltage and under voltage protective device

## ▶ 产品描述 Description



The self-reset over voltage and under voltage protective device considered modular design. The circuit board adopted good quality Latching relays and others components with reliable performance. When the power supply is unstable (voltage is too high or too low), the protection function will be activated automatically. Once the voltage exceeds the limited range, it will be cut off automatically, so that to protect the peoples and electrical appliances /equipment in safe, also the protective device will be reset by itself in 60 seconds, when the power returns to normal.

## ▶ 技术指标 Technical index

Rated AC voltage 额定电压	380±10% VAC, Frequency 50HZ
Max current 最大电流	63A
Over voltage action cut off value 过压启动值	>460 ±5VAC
Reset voltage value after normal voltage 常压恢复值	420-440VAC
Under voltage action cut off value 欠压启动值	<300 ±5VAC
Reset voltage value after normal voltage 常压恢复值	335 ±5VAC
Electricity reset time after normal voltage 过欠压启动时间	<60\$
Power consumption 自身消耗	<2W
Electrical life 电气寿命	1×10 <sup>5</sup> Cycles 次
Mounting 安装	DIN RAIL TH35mm
Dimension 尺寸	L=77.5mm W73mm H66mm

## ▶ 产品外形尺寸 Outlie dimensions



